HASIL CEK_60010313_(13)

by Sunardi 60010313

Submission date: 10-Dec-2020 09:37AM (UTC+0700)

Submission ID: 1470457901

File name: CEK13_60010313.pdf (992.08K)

Word count: 4830

Character count: 19549





Market Basket Analysis to Identify Stock Handling Patterns and Item Arrangement Patterns Using Apriori **Algorithms**

Sunardi^{*}, Abdul Fadlil, Tresna Yudha Prawira

Masters Informatics Technology Universitas Ahmad Dahlan Yogyakarta *sunardi@mti.uad.ac.id

Abstract-The process of managing the pattern of handling stock of goods and the pattern of arranging goods on store shelves requires an identification process by utilizing data from sales transaction results. Market basket analysis of z es transaction data using Apriori Algorithm stages produces an information in the form of association rules with a minimum support value of 50% and a minimum confidence of 60%. It can be a reference in the arrangement of items on store shelves by referring to a combination of items that are often bought by consumers simultaneously. In addition, the stock inventory pattern can take advantage of the results of determining the high frequency value in the combination pattern 1 - itemset C1 with a minimum support value of 50% which is compared with the initial

Keywords: Apriori Algorithm, arrangement of goods, stock

1. Introduction

In the management of a minimarket, it is necessary to have a system management in the process of handling the patterns of stock handling and patterns of arrangement of goods, with the aim of structuring the goods to make it easier for customers to shop and patterns of handling stock of goods to provide the availability of goods needed by customers. Of the two, if not handled by an analysis of sales transaction data, it can be a problem for the development of minimarkets. Many business sellers of goods that assume that the sales transaction data report is only to be a report on several things, such as how many items are sold, how many items are still available, and how much profit is obtained. Sales transaction data can be used to help decisions in predicting the layout of goods so that consumers easily find the items sought and determine the prediction of the amount of stock in the future. These problems can be solved by market basket analysis using the stages of Apriori Algorithm, namely by identifying the value of support and confidence of goods sold at the minimarket. It can be a preference in the pattern of arrangement of goods based on customer habits in buying goods simultaneously and can also be a prediction of the stock of goods in the future [1].

Market basket analysis is the process of analyzing customer buying habits on each sales transaction data, by identifying associations between different items of the consumer shopping basket [2].

This research focuses on the event identifying the process of managing stock patterns of handling goods and structuring patterns of goods using Apriori Algorithm. This algorithm is used to find rules or measure the relationship between two or more items. Associative rules are expressed in terms of if they are antecedents, so they are consistent with the amount of support and confidence associated with the rules [3].

In a study entitled "Implementation of Apriori Algorithms with market basket analysis for product layout settings" explained that the association rules formed from the results of the discussion are used to regulate product placement in stores. Products that have high associations with other products will be placed close together, so as to facilitate consumers in buying products and store management in managing stock [4]. Maharani, et al. Also conduct research under the heading "Implementation of data mining for minimarket layout by applying association rule". The research aims to apply the association rule in the preparation of product layouts. From the rules generated, it can help companies in the preparation

of product layouts [5]. Meanwhile, according to research conducted by Adyawangkara, et al with the title "Analysis of the rules of association between items in purchase transactions using data mining with Apriori Algorithm (case study: Gunungan minimarket, Central Java)", in that study aims to find the rules of association in the purchase of items in minimarkets to solve the problem of procurement of goods stock, determining promotional strategies, and arranging goods in minimarkets [6]. Research on the rules of association between items in identifying products that are sold and the relationship between products based on the conditions of the sales transaction data. [7] [8] [9] [10] [11] [12] [13] [14] [15].

Research Methods

This study conducted an experimental process with the aim of understanding the steps in the market basket analysis process using Apriori Algorithms in identifying patterns of handling stock items and patterns of arrangement of goods on store shelves. The stages in this study can be shown by Figure 1:



Figure 1. Research Process Stage

Data Collection Stage

The data used in this study were taken from the sales transaction database that is available at the Surya Mart minimarket. The mini market is a campus cooperative located at STMIK Muhammadiyah Paguyangan Brebes which is located on Jl. Pangeran Diponegoro, Kec. Paguyangan, Kab. Brebes. Postal Code 52276.

Data Processing Stage

At this stage the database scan process is carried out from the sales transaction table in order to calculate the number of purchases that occur on each item of goods. After that, the process is implemented into tabular data in the form of binary data with the statement 0 if the item was not purchased and 1 if the item was purchased on each item sales transaction identity.

Market Basket Analysis Phase Using Apriori Algorithms.

From the tabular data generated at the data processing stage, a market basket analysis process is performed using Apriori Algorithm to find high frequency values of sales transaction data by identifying support values and determining a minimum support value of 50%. The next step is to establish a 2-item A pociation containing B by finding a confidence value, and determining a minimum confidence value of 60%. Figure 2 shows the completion stage of the market basket analysis process using apriori algorithm:




Figure 2. Market Basket Analysis Phase Using Apriori Algorithms.

Results Determination Stage

The final stage of this research is the process of determining the pattern of handling stock of goods and the arrangement of goods on store shelves from the results of the market basket analysis process using Apriori Algorithm in sales transaction data.

Results and Discussion

Data collection stage

At this stage the data collection process is carried out from the database, in the form of sales data at the solar mart minimarket during the 1 (one) month transaction period as shown in Figure 3:

	to trover 📝 SQL Editor							Object search
d.qtg_item as QCA b.cab_name as CACA FROM TB_TRANS_FEE JOSEN TB_CACAGE b (JOSEN TB_DECAMAL o JOSEN TB_DETAIL_THE	TITY, a.tql_trans_ MS_TRASSASI, c.pep MILLS a MS (a.id_tabang_pen) ON (a.id_papewai_pen) ON (a.id_bapaewai_pen) MS_OS_INDEXLISS_d ON (B.)	penb as TAUGOA 2_tame as PEGAO b=b.id_cabang) mb=c.id_popea (e.id_trans_per	TRANSARSI, m.vali RI_RASIR			id_barang	as HO_MANNS, e.baran	g_name as 1369_138365,
ID_TRANSAKSI	ID_DETAIL_TIWNS	NO_BARVANG	NAMA_BARUNG	QUANTITY	TANGGAL_TR.	MAKTU	CASANG_TRANSAKSI	PEGAWA_KASIR
PEMB01	DTPEMB0001	GL1001	Gule-Jeve 1 Ko		2019-12-64	09:11:00	SuveMet A	M. Jafor Solmen
PEMBO1	DTPEMBD002	BR1111	Decas Murah 5 Kg		2 2019-12-64	09:11:00	SuyaMatA	M. Jafar Salman
PEMB01	DTPEMB0003	ASL 101	Air Minum Karnsson		2018-12-64	09:11:00	SuryaMart.A	M. Jafer Selmen
PEMB02	DTPEMB0004	GL1002	Gule-Jeve 1/2 Kg		5 2019-12-64	09:15:00	SuyaMatA	M. Jafor Salman
PEMBI22	DIPEMBOODS	0000001	Kopi Hillam 1/2 Kg		2010-12-04	09:15:00	SuyaMatA	M. Jatar Salman
PEMB32	DTPEMB0006	00000002	Gule Perir 1 Kg		2 2018-12-64	09:15:00	SuyaMart.A	M. Jafer Selmen
PEMB02	DTPEMB0007	ASL 102	Air Minum Batol 600	9	2019-12-64	09:15:00	SuyaMatA	M. Jafer Selman
PEMBOO	DIPEMBOOOD	0000000	Gula Pasir 1.0 Kg		5 2016-12-64	09:30:00	SuyaMatA	M. Jafar Salman
PEMB03	DTPEMB0009	ASL103	Air Minum Deles		2 2018-12-64	09:30:00	SuyaMart.A	M. Jafer Selmen
PEMB03	DTPEMB0010	8R1112	Beras Premium \$16;		2019-12-64	09:30:00	SuyaMart.A	M. Jafer Selman
PEMEDS	DTPEMBEOD104	0811111	Dense Hursh 5 Kg		2 2010-12-11	09:00:00	Surya/Nart.A	M. Jafar Salman
PEMB35	DTPEMB00105	ASL101	Air Minum Kernsson		2 2018 12-11	09:00:00	SuyaMart.A	M. Jefer Selmen
PEMB35	DTPEM800106	ASL103	Air Minum Gelas		2019-12-11	09:00:00	SuyaMatA	M. Jafer Selman
PEMEDS	DTPEMBOO107	GL1002	Quin Java 10 Kg		5 2016-12-11	09:00:00	SuyaMatA	M. Jafar Salman
PEMB04	DTPEMB0011	8R1111	Beree Mureh 5 Kg		2 2018 12 64	09:45:00	SuyaMatA	M. Jafor Solmen
PEMB37	DTPEMECO110	ASL 102	Air Minum Batol 600	3	2019-12-12	08:00:00	SwyaMatA	M. Jafor Solman
PEMELI7	DTPEMB00111	CA.1002	Quie Jeve 10 Kg		2016-12-12	08:90:90	SuyaMatA	M. Jater Salman
PEMB38	DTPEMB00112	GL1001	Gule Jeve 1 Kg		3 2018 12-12	10:00:00	SuyaMart.A	M. Jafor Solmen
PEMB38	DTPEMECO113	8R1111	Beras Murah 5 Kg		2 2019-12-12	10:00:00	SuyaMat.A	M. Jater Selman
PEMESS	DTPEMB00114	ASL 103	Air Minum Gelas		2 2016-12-12	10:00:00	SuyaMatA	M. Jafar Salman
PEMB38	DTPEMB00116	0000003	Gule Perir 1/2 Kg		8 2018 12:12	10:00:00	SunaMet A	M. Jafor Solman

Figure 3. Data from the simulation of sales transactions.

After that, the data processing stage is carried out by scanning the database and changing it into tabular data.

Data Processing Stage

Data processing stage is done by scanning the database of sales transaction data, namely by identifying the number of items purchased at each transaction id, information Y and N on each item explains if "Y" means the item was purchased and if "N" means the item is not bought. Data is presented in tabular form as in table 1:

Table 1. Number of items in each transaction id.

Transaction ID	Black Coffee 1/2 Kg	Granulated Sugar 1 Kg	Granulated Sugar 1/2 Kg	Gallon Bottled Water	600 ml Bottled Water	Glass drinking water	Cheap rice 5 kg	Premium Rice 5 Kg	Javanese Sugar 1 Kg	Java Sugar 1/2 Kg
PEMB01	Y	Y	Y	Y	N	N	Y	N	Y	N
PEMB02	N	Y	N	N	Y	N	N	Y	Y	Y
PEMB03	N	Y	N	N	N	Y	N	Y	Y	N
PEMB04	Y	Y	Y	N	N	N	Y	Y	N	N
PEMB10	Y	N	N	Y	N	N	N	N	Y	Y
PEMB11	Y	N	Y	N	N	N	Y	Y	Y	Y
PEMB15	Y	N	Y	Y	N	N	Y	Y	Y	Y
PEMB16	N	Y	Y	Y	Y	Y	Y	N	N	N
PEMB19		Y	N	Y	Y	N	N	N	N	N
	N Y	Y	Y	N		N	Y		Y	N
PEMB20					N			Y		
PEMB23	N	Y	Y	Y	N	N	Y	N	Y	N
PEMB24	Y	N	N	Y	Y	N	Y	Y	N	Y
PEMB27	N	Y	Y	N	N	N	Y	N	Y	Y
PEMB28	Y	N	N	N	N	N	Y	Y	Y	N
PEMB31	N	N	N	Y	N	N	Y	Y	Y	N
PEMB32	Y	Y	Y	\mathbf{Y}	N	N	Y	Y	N	Y
PEMB35	N	N	Y	\mathbf{Y}	N	Y	Y	N	Y	Y
PEMB37	Y	Y	Y	Y	Y	N	Y	N	N	Y
PEMB38	N	N	Y	N	N	\mathbf{Y}	Y	N	Y	N
PEMB41	Y	Y	Y	Y	N	Y	N	N	Y	N
PEMB43	Y	Y	Y	1	Y	N	N	N	N	N
PEMB44	Y	Y	N	N	N	N	Y	Y	N	Y
PEMB47	Y	Y	N	N	N	Y	N	Y	N	N
PEMB49	N	N	N	N	N	N	Y	Y	N	N
PEMB50	N	N	Y	Y	N	N	Y	N	Y	N
PEMB53	Y	Y	N	N	Y	N	Y	N	Y	N
PEMB55	N	N	N	Y	N	N	N	Y	N	Y
PEMB56	Y	Y	Y	N	N	Y	N	N	N	N
PEMB59	N	N	N	N	N	N	Y	Y	N	N
PEMB61	Y	Y	N	N	N	1	N	Y	N	N
PEMB62	N	N	Y	N	Y	N	Y	N	N	N
PEMB65	N	N	N	Y	N	N	N	Y	Y	N
PEMB67	N	Y	N	N	N	N	Y	N	N	N
PEMB68	N	N	Y	Y	N	N	N	N	Y	N
PEMB71	N	Y	N	N	N	Y	Y	N	N	N
PEMB73	N	N	N	Y	N	N	Y	Y	Y	N
PEMB74	Y	Y	N	N	N	N	N	N	Y	N
PEMB77	N	N	Y	Y		N	N	Y	Y	N
PEMB79	Y	N	Y	Y	2 N	N	Y	N	N	Y
PEMB80	N	Y	N	N	N	Y	N	N	N	N
PEMB81	Y	Y	Y	Y				Y	Y	N
PEMB81	N	N	N	N	N N	N Y	N Y	Y	N	N
PEMB88	Y	N	Y	Y	N	N	Y	N	Y	N
PEMB88	N	N N			N		N	Y		
			N	Y		Y			N	N N
PEMB91	Y	Y	Y	Y	N	N	N	Y	N	N
PEMB92	Y	Y	Y	Y	Y	N	N	Y	Y	N
PEMB95	N	N	Y	Y	N	N	N	N	Y	N
PEMB97	Y	Y	Y	Y	N	N	N	Y	Y	N
PEMB98	Y	Y	Y	Y	N	N	N	Y	Y	N
PEMB99	Y	N	Y	N	N	N	N	Y	N	N

From the data in Table 1 which contains the items column Y = 1 and N = 0 with the aim that it is easy to count each with information Y and N, it is changed in binary form to tiem on each transaction, as shown in Table 2:

Table 2. The number of transaction items is changed in binary form.

Transaction ID	Black Coffee	Granulated	Granulated	Gallon	600 ml Bottled	Glass drinking	Cheap	Premium	Javanese Sugar 1	Java Sugar 1/2
Transaction 115	1/2 Kg	Sugar 1 Kg	Sugar 1/2 Kg	Bottled Water	Water	water	rice 5 kg	Rice 5 Kg	Kg	Kg Kg
PEMB01	1	1	1	1	0	0	1	0	1	0
PEMB02	0	1	0	0	1	0	0	1	1	1
PEMB03	0	1	0	0	0	1	0	1	1	0
PEMB04	1	1	1	0	0	0	1	1	0	0
PEMB10	1	0	0	1	0	0	0	0	1	1
PEMB11	1	0	1	0	0	0	1	1	1	1
PEMB15	1	0	1	1	0	0	1	1	1	1
PEMB16	0	1	1	1	1	1	1	0	0	0
PEMB19	0	1	0	1	1	0	0	0	0	0
PEMB20	1	1	1	0	0	0	1	1	1	0
PEMB23	0	1	1	1	0	0	1	0	1	0
PEMB24	1	0	0	1	1	0	1	1	0	1
PEMB27	0	1	1	0	0	0	1	0	1	1
PEMB28	1	0	0	0	0	0	1	1	1	0
PEMB31	0	0	0	1	0	0	1	1	1	0
PEMB32	1	1	1	1	0	0	1	1	0	1
PEMB35	0	0	1	1	0	1	1	0	1	1
PEMB37	1	1	1	1	1	0	1	0	0	1
PEMB38	0	0	1	0	0	1	1	0	1	0
PEMB41	1	1	1	1	0	1	0	0	1	0
PEMB43	1	1	1	1	1	0	0	0	0	0
PEMB44	1	1	0	0	0	0	1	1	0	1
PEMB47	1	1	0	0	0	1	0	1	0	0
PEMB49	0	0	0	0	0	0	1	1	0	0
PEMB50	0	0	1	1	0	0	1	0	1	0
PEMB53	1	1	0	0	1	0	1	0	1	0
PEMB55	0	0	0	1	0	0	0	1	0	1
PEMB56	1	1	1	0	0	1	0	0	0	0
PEMB59	0	0	0	0	0	0	1	1	0	0
PEMB61	1	1	0	0	0	1	0	1	0	0
PEMB62	0	0	1	0	1	0	1	0	0	0
PEMB65	0	0	0	1	0	0	0	1	1	0
PEMB67	0	1	0	0	0	0	1	0	0	0
PEMB68	0	0	1	1	0	0	0	0	1	0
PEMB71	0	1	0	0	0	1	1	0	0	0
PEMB73	0	0	0	1	0	0	1	1	1	0
PEMB74	1	1	0	0	0	0	0	0	1	0
PEMB77	0	0	1	1	0	0	0	1	1	0
PEMB79	1	0	1	1	0	0	1	0	0	1
PEMB80	0	1	0	0	0	1	0	0	0	0
PEMB81	1	1	1	1	0	0	0	1	1	0
PEMB82	0	0	0	0	0	1	1	1	0	0
PEMB88	1	0	1	1	0	0	1	0	1	0
PEMB89	0	0	0	1	0	1	0	1	0	0
PEMB91	1	1	1	1	0	0	0	1	0	0
PEMB92	1	1	1	1	1	0	0	1	1	0
PEMB95	0	0	1	1	0	0	0	0	1	0
PEMB97	1	1	1	1	0	0	0	1	1	0
PEMB98	1	1	1	1	0	0	0	1	1	0
PEMB99	1	0	1	0	0	0	0	1	0	0
Total Items Sold	26	27	28	28	9	12	27	27	27	12

1) Market Basket Analysis Phase Using Apriori 5 Algorithms.

Analysis of high frequency patterns

gigh frequency pattern analysis is done by finding a combination of items that meet the minimum requirements of the support value in the transaction data. The data in Table 3 shows the results of the number of transactions in each itemset:

Table 3. List of itemset.

Numb	Code BR	Name BR	Total Transactions	Initial Inventory	Stock Available
1	0000001	Black Coffee 1/2 Kg	26	45	19
2	0000002	Granulated Sugar 1 Kg	27	30	3
3	0000003	Granulated Sugar 1/2 Kg	28	40	12
4	ASL101	Gallon Bottled Water	28	80	52
5	ASL102	600 ml Bottled Water	9	240	231
6	ASL103	Glass drinking water	12	40	28
7	BR1111	Cheap rice 5 kg	27	40	13
8	BR1112	Premium Rice 5 Kg	27	40	13
9	GL1001	Javanese Sugar 1 Kg	27	40	13
10	GL1002	Java Sugar 1/2 Kg	12	60	48

The next step is to calculate the value of support in combination with 1 - itemset or C_1 using equation (1):

$$Support(A) = \frac{Number of Transactions Containing A}{Transaction Total}$$
(1)

The ults of determining the support value of each item can be seen in table 4:

Table 4. Results for 1- itemset support values

			• • •	
NUMB	Code BR	Name BR	Total Transactions	Support (%)
1	0000001	Black Coffee 1/2 Kg	26	52
2	0000002	Granulated Sugar 1 Kg	27	54
3	0000003	Granulated Sugar 1/2 Kg	28	56

NUMB	Code BR	Name BR	Total Transactions	Support (%)
4	ASL101	Gallon Bottled Water	28	56
5	ASL102	600 ml Bottled Water	9	18
6	ASL103	Glass drinking water	12	24
7	BR1111	Cheap rice 5 kg	27	54
8	BR1112	Premium Rice 5 Kg	27	54
9	GL1001	Javanese Sugar 1 Kg	27	54
10	GL1002	Java Sugar 1/2 Kg	12	24

The next step is to identify a combination pattern with a minimum support of 50%, then the process of forming 2 - itemset or C_2 with a minimum support of 50% as shown in table 5.

 $\label{eq:combination} Table \ 5. \ Combination \ patterns \ of \ C_1 \ with \ a \ minimum \\ support \ of \ 50\%.$

Numb	Code BR	Name BR	Total Transactions	Support (%)
1	0000001	Black Coffee 1/2 Kg	26	52
2	0000002	Granulated Sugar 1 Kg	27	54
3	0000003	Granulated Sugar 1/2 Kg	28	56
4	ASL101	Gallon Bottled Water	28	56
5	BR1111	Cheap rice 5 kg	27	54
6	BR1112	Premium Rice 5 Kg	27	54
7	GL1001	Javanese Sugar 1 Kg	27	54

Calculation of support values using a 2-itemset combination using equation (2):

 $Support(A,B)=P(A\cap B)$

Support(A, B) =
$$\frac{\sum transaction\ contains\ A\ and\ B}{\sum Total\ Transactions}$$
 (2)

Table 6. Minimum support values of 50% of the 2-itemset combination

Numb	Item Name	Amount	Support (%)
1	Black Coffee 1/2 Kg → Granulated Sugar 1 Kg	19	38
2	Black Coffee 1/2 Kg \rightarrow Granulated Sugar 1/2 Kg	18	36
3	Black Coffee 1/2 Kg \rightarrow Gallon Bottled Drinking Water	5	10
4	Black Coffee 1/2 Kg \rightarrow Cheap Rice 5 Kg	12	24
5	Black Coffee 1/2 Kg \rightarrow Premium Rice 5 Kg	16	32
6	Black Coffee 1/2 Kg \rightarrow Java Sugar 1 Kg	14	28
7	Granulated Sugar 1 Kg \rightarrow Granulated Sugar 1/2 Kg	16	32
8	Granulated Sugar 1 Kg \rightarrow Gallon Bottled Drinking Water	13	26
9	Granulated Sugar 1 Kg \rightarrow Cheap Rice 5 Kg	12	24
10	Granulated Sugar 1 kg \rightarrow Premium Rice 5 kg	13	26
11	Granulated Sugar 1 kg \rightarrow Javanese Sugar 1 kg	13	26
12	Gallon Bottled Drinking Water \rightarrow Cheap Rice 5 Kg	13	26
13	Gallon Bottled Drinking Water \rightarrow Premium Rice 5 Kg	14	28
14	Gallon Bottled Drinking Water \rightarrow Java Sugar 1 Kg	18	36
15	Cheap Rice 5 Kg \rightarrow Premium Rice 5 Kg	13	26
16	Cheap Rice 5 Kg → Java Sugar 1 Kg	15	30
17	Premium Rice 5 Kg \rightarrow Java Sugar 1 Kg	12	24

In the process of forming a 2-itemset combination pattern no one meets the minimum support value of 50%, then a 1-itemset combination can be met for the formation of associative rules.

2) Establishment of associative rules

After a minimum support value of 50% of the C_1 combination is determined, an associative

rule is sought that meets the minimum confidence requirement of candidate 2 item A containing B in each itemset. The confidence value of the associative rule 2 - item $A \rightarrow B$ is obtained using equation (3):

Confidence (A,B)=

$$P(B|A) = \frac{Number\ of\ transactions\ containing\ A\ and\ B}{Number\ of\ transactions\ containing\ A} \tag{3}$$

Table 7. Confidence values from forming 2-item associative rules $A \rightarrow B$.

Numb	Itemset	Amount	Confident (%)
1	(0000001, Black Coffee 1/2 Kg), (0000002, 1 Kg Granulated Sugar)	18	69,23
2	(0000001, Black Coffee 1/2 Kg), (0000003, Granulated Sugar 1/2 Kg)	18	69,23
3	(0000001, Black Coffee 1/2 Kg), (ASL101, Gallon Bottled Drinking Water)	15	57,69
4	(0000001, Black Coffee 1/2 Kg), (BR1111, Cheap Rice 5 Kg)	13	50,00
5	(0000001, Black Coffee 1/2 Kg), (BR1112, Premium Rice 5 Kg)	16	61,53
6	(0000001, Black Coffee 1/2 Kg), (GL1001, Javanese Sugar 1 Kg)	14	53,84
7	(0000002, 1 Kg Granulated Sugar), (0000003, 1/2 Kg Granulated Sugar)	16	59,25
8	(0000002, 1 Kg Granulated Sugar), (ASL101, Gallon Bottled Drinking Water)	13	48,14
9	(0000002, 1 Kg Granulated Sugar), (BR1111, Cheap Rice 5 Kg)	12	44,44
10	(0000002, 1 Kg Granulated Sugar), (BR1112, Premium Rice 5 Kg)	13	48,18
11	(0000002, 1 Kg Granulated Sugar), (GL1001, 1 Kg Java Sugar)	13	48,14
12	(0000003, Granulated Sugar 1/2 Kg), (ASL101, Gallon Bottled Drinking Water)	20	71,42

Numb	Itemset	Amount	Confident (%)
13	(0000003, Granulated Sugar 1/2 Kg), (BR1111, Cheap Rice 5 Kg)	16	57,14
14	(0000003, Granulated Sugar 1/2 Kg), (BR1112, Premium Rice 5 Kg)	12	42,85
15	(0000003, Granulated Sugar 1/2 Kg), (GL1001, Java Sugar 1 Kg)	18	64,28
16	(ASL101, Gallon Bottled Water), (ASL102, 600ml Bottled Water)	6	21,42
17	(ASL101, Gallon Bottled Drinking Water), (BR1111, Cheap Rice 5 Kg)	13	46,42
18	(ASL101, Gallon Bottled Drinking Water), (BR1112, Premium Rice 5 Kg)	14	50,00
19	(ASL101, Gallon Bottled Drinking Water), (GL1001, Java Sugar 1 Kg)	18	64,28
20	(BR1111, Cheap Rice 5 Kg), (BR1112, Premium Rice 5 Kg)	13	48,14
21	(BR1111, Cheap Rice 5 Kg), (GL1001, Java Sugar 1 Kg)	14	51,85
22	(BR1112, Premium Rice 5 Kg), (GL1001, Java Sugar 1 Kg)	14	51,85

Next is determining the minimum confidence value of 60%, the confidence value of 2 - items $A \to \, B$

that will qualify for the determination of association rules has a confidence value above 60%.

Table 8. Value of Association rules with a minimum value of 60% confidence.

Numb	Itemset	Amount	Confident (%)
1	(0000001, Black Coffee 1/2 Kg) \rightarrow (0000002, 1 Kg Granulated Sugar)	18	69,23
2	(0000001, Black Coffee 1/2 Kg) \rightarrow (0000003, Granulated Sugar 1/2 Kg)	18	69,23
3	(0000001, Black Coffee 1/2 Kg) \rightarrow (BR1112, Premium Rice 5 Kg)	16	61,53
4	(0000003, Granulated Sugar 1/2 Kg) \rightarrow (ASL101, Gallon Bottled Drinking Water)	20	71,42
5	(0000003, Granulated Sugar 1/2 Kg) \rightarrow (GL1001, Java Sugar 1 Kg)	18	64,28
6	(ASL101, Gallon Bottled Drinking Water) \rightarrow (GL1001, Java Sugar 1 Kg)	18	64,28

Table 9. Results of determining the pattern of handling stock of goods.

NUMB	KODE BR	NAME BR	TOTAL TRANSACTIONS	SUPPORT (%)	INITIAL INVENT- ORY	ADDITI-ON STOCK
1	0000001	Black Coffee 1/2 Kg	26	52	45	23
2	0000002	Granulated Sugar 1 Kg	27	54	30	16
3	0000003	Granulated Sugar 1/2 Kg	28	56	40	22
4	ASL101	Gallon Bottled Water	28	56	52	29
5	BR1111	Cheap rice 5 kg	27	54	40	22
6	BR1112	Premium Rice 5 Kg	27	54	40	22
7	GL1001	Javanese Sugar 1 Kg	27	54	40	22

Table 10. Association Rules

Numb	Rules	Confidence %
1	If you buy ½ Kg Black Coffee then buy 1 Kg Granulated Sugar	69,23
2	If you buy ½ Kg Black Coffee then buy ½ Kg Sugar	69,23
3	If you buy ½ Kg Black Coffee then buy 5 Kg Premium Rice	61,53
4	If you buy ½ Kg Granulated Sugar then buy Gallon Bottled Drinking Water	71,42
5	If you buy ½ Kg Granulated Sugar then buy 1 kg of Java Sugar	64,28
6	If you buy Gallon Bottled Drinking Water then buy Java Sugar 1 Kg	64,28

c. Results Determination Stage

From the results of the analysis of determining the value of support and confidence, it can be concluded the results of the pattern of handling stock of goods and arrangement of goods on the store shelf, as follows:

Pattern of handling stock of goods
 From the results of determining the minimum support value of 50% in the 1-itemset combination pattern, it can be identified the addition of stock items with a percentage:

Stock Addition =
$$\frac{Initial\ inventory}{Value\ of\ Support\ (\%)} x\ 100\%$$
 (4)

From Table 9 results can be drawn from the stage of identifying the pattern of handling stock of goods utilizing a minimum value of support of 50% of the combination of 1-itemset, by calculating the initial inventory is compared with the value of support so that it can be identified in the item stock increase column in Table 9.

2. Pattern of Arrangement of Goods
From the results of the analysis in identifying the handling of the layout of the goods a ing Apriori Algorithm, it can be determined from the minimum value of 50% support and the minimum value of Confidence 60% which produces the following association rules:

From Table 10. it can be identified the tendency of customer purchases, it is known that the tendency of customers if buying Black Coffee items ½ Kg is most likely with a Confidence value of 69.23% customers will also buy 1 Kg Granulated Sugar. from this tendency can be a strategy to arrange the layout of the item with the pattern of Black Coffee ½ Kg brought closer to 1 Kg Granulated Sugar, Black Coffee ½ Kg closer to Granulated Sugar ½ Kg and so on, so that customers can easily find the items they need.

4. Conclusion

Based on the analysis phase of the results and discussion above, it can be concluded that identification of patterns of handling stock of goods and arrangement of goods can utilize data on the results of sales transactions. And then, analysis of high frequency patterns with a minimum support value of 50% from a combination of 1 - itemset C1 can determine the pattern of handling stock of goods, namely by balancing the initial inventory with a support value so that the prediction results of adding stock will be obtained. Beside that, the results of the formation of association rules that are determined from a minimum value of 50% support and a minimum value of 60% confidence can produce a tendency of customers to buy items, so that these tendencies can be a reference in the process of item layout by arranging items close together.

References

- A. Junaidi, "Implementasi Algoritma Apriori dan FP-Growth untuk Menentukan Persediaan Barang," *Jurnal Sisfokom (Sistem Informasi dan Komputer)*, vol. 8, no. 1, pp. 61-67, Maret 2019.
- [2] H. Jiawei dan K. Micheline, *Data Mining: Concept and Techniques Second Edition*, Morgan Kaufman Publishers, 2006.
- [3] D. T. Larose, Discovering knowledge in data: an introduction data mining, Jhon Wiley & Sons Inc, 2005.
- [4] Suprayogi, dan A. Karima, "Implemetasi Algoritma Apriori dengan Market Basket Analysis untuk Pengaturan Tata Letak Produk," *Jurnal SISFOTENIKA*, vol. 9, no. 2, pp. 169-179, Juli 2019.
- [5] Maharani, N. A. Hasibuan, dan N. Silalahi, "Implementasi Data Mining untuk Pengaturan Layout Minimarket dengan Menerapkan Association Rule," *Jurnal Riset Komputer*, vol. 4, no. 4, pp. 6-11, Agustus 2017.
- [6] A. K. Prasidya, dan C. Fibriani "Analisis Kaidah Asosiasi Antar Item Dalam Transaksi Pembelian Menggunakan Data Mining Dengan Algoritma Apriori (Studi Kasus Gun Bandungan Jawa Tengah," Jurnal Ilmiah Teknologi Informasi, vol. 14, no. 2, pp. 173-184, Juli 2017.
- [7] M. Sholik, dan A. Salam, "Implementasi Algoritma Apriori untuk Mencari Asosiasi BArang yang Dijual di E-commerce OrderMAs," *Jurnal Techno. Com*, vol. 17, no. 2, pp. 158-170, Mei 2018.
- [8] G. Abdurrahman, "Analisis Aturan Asosiasi Data Transaksi Supermarket Menggunakan Algoritma Apriori," *Jurnal Sistem dan Teknologi Informasi Indonesia*, vol. 2, no.2, pp. 100-111, Agustus 2017
- [9] R. Yanto, dan R. Khorirah, "Implementasi Data Mining dengan Metode Algoritma Apriori dalam Menentukan Pola Pembelian Obat," *Creative Information Technology Journal*, vol. 2, no. 2, pp. 102-113, April 2015.
- [10] S. Wahyuni, Suherman, dan L. P. Harahap, "Implementasi Data Mining dalam Memprediksi Stok Barang Menggunakan Algoritma Apriori," *Jurnal Teknik dan Informatika*, vol. 5, no.2, pp. 67-71, Juli 2018.
- [11] E. D. Sikumbang, "Penerapan Data Mining Penjualan Sepatu Menggunakan Metode Algoritma Apriori," *Jurnal Teknik Komputer*, vol. 4, no. 1, pp. 156-161, Februari 2018.
- [12] Y. Suardi, B. F. Ahmad, M. Ita, dan W. Bambang,

- "Penerapan Data Mining Pengaturan Pola Tata Letak Barang pada Berkah Swalayan untuk Strategi Penjualan Menggunakan Algoritma Apriori," *Jurnal Teknologi Sistem Informasi dan Sistem Komputer TGD*, vol. 2, no. 1, pp. 69-75, Januari 2019.
- [13] A. Cep, H. Nila, dan W. Wiwiek, "Implementasi Data Mining Penjualan Kosmetik Pada Toko Zahrani Menggunakan Algoritma Apriori," Sentra Penelitian Engineering dan Edukasi, vol. 11, no. 2, pp. 1-7, Mei 2019.
- [14] B. A. Pilipus, R. J. Ekik, dan L. Yonata, "Prediksi Pola Pembelian *Customer* dengan *Market Basket Analysis* pada PT. Capella Medan," *Jurnal Sistem Informasi dan Komputer*, vol. 2, no. 2, pp. 59-66, Maret 2019.
- [15] Y. S. Haysrif, Rismayani, dan L. S Novita, "Data Mining Menggunakan Algoritma Apriori untuk Analisis Penjualan," Seminar Ilmiah Sistem Informasi Dan Teknologi Informasi, vol. 6, no. 1, pp. 217-226, Agustus 2019.

ORIGINALITY REPORT

SIMILARITY INDEX

10%

5%

7%

RITY INDEX INTERNET SOURCES

PUBLICATIONS

STUDENT PAPERS

PRIMARY SOURCES

1 archive.org

4%

www.gamefaqs.com

3%

Submitted to Universitas PGRI Madiun
Student Paper

2%

Yusuf Kurnia, Yohanes Isharianto, Yo Ceng Giap, Aditiya Hermawan, Riki. "Study of application of data mining market basket analysis for knowing sales pattern (association of items) at the O! Fish restaurant using apriori algorithm", Journal of Physics: Conference Series, 2019

1%

Publication

Reza Alfianzah, Rani Irma Handayani, Murniyati Murniyati. "Implementation of Apriori Algorithm Data Mining for Increase Sales", SinkrOn, 2020

1%

Publication

Exclude quotes On Exclude matches < 1%

Exclude bibliography Off