

Application of Cellulose Acetate Propionate Biopolymer Membrane in The Treatment of Textile Wastewater Containing Remazol Dye

By Maryudi Maryudi



Application of Cellulose Acetate Propionate Biopolymer Membrane in The Treatment of Textile Wastewater Containing Remazol Dye

Amillia¹, Maryudi^{1,✉}, Aster Rahayu¹, Dhias Cahya Hakika¹, Siti Samahani Suradi²

DOI: <https://doi.org/10.15294/jbat.v13i1.50295>

¹Chemical Engineering, Faculty of Industrial Technology, State Ahmad Dahlan University, Jalan Ringroad Selatan, Kragilan, Tamanan, Banguntapan Sub-district, Bantul Regency, Yogyakarta Special Region, 55191, Indonesian

²Department of Science and Mathematics, Centre for Diploma Studies, Universiti Tun Hussein Onn Malaysia, Pagoh Higher Education Hub, 84600, Pagoh, Johor, Malaysia

Article Info

Article history:
Received
14 March 2024
Revised
21 May 2024
Accepted
5 June 2024
Online
June 2024

Keywords:
Cellulose acetate
propionate;
Membrane;
Phase inversion;
Remazol dye;
Rejection

Abstract

Textile liquid waste is pollution resulted from textile industry activities that often produce hazardous and toxic materials. Therefore, appropriate processing techniques are needed. There are many processing methods that can be used in treating this textile liquid waste, one of which is using membrane technology with phase inversion techniques. Membrane technology has advantages over other processing methods such as, being biopolymeric, relatively lower energy consumption, does not use chemicals in the processing process, and does not cause new waste in the processing process. In this study, 3 variations of cellulose acetate propionate (CAP) concentration were carried out in the manufacture of membranes including, 13% CAP; 14% CAP; and 15% CAP. Membranes that have been made are then carried out several analyses, namely porosity analysis; flux analysis; rejection analysis; and color concentration reduction analysis. The results in this study found that the highest porosity value, rejection value and flux value were found in the CAP membrane with a concentration of 13%. The CAP membrane has the best rejection value on reducing the remazol concentration of 43% with a membrane of 13% CAP.

INTRODUCTION

16
Liquid waste from the textile industry is pollution resulting from textile industry activities that often produce hazardous and toxic materials (B3) (Kishor et al., 2021; Rizkiah & Luciana, 2022; Yuniarti & Widayatno, 2022) and these wastes are non-biodegradable and resistant to good physical-chemical treatment methods (Enrico, 2019; Rizkiah & Luciana, 2022; Sausan et al., 2021; Sunoko, 2018). In the production of the textile industry, out of 100% of the dyes used in fact only 5% of dyes are effectively used. One type of dye that is often used in the textile industry is Remazol type dye (Amelia

et al., 2023; Subagyo, 2021; Rahmiati et al., 2018) (Ismail et al., 2019).

Remazol is a textile dye with the molecular formula C₁₈H₁₄N₂Na₂O₁₀S₃ with a molecular weight of 560.5 g/mol (Yuniarizky & Nazriati, 2021). The impact of remazol dyes on humans includes eye irritation, skin irritation, cancer, carcinogenic, mutagenic, and has a high synthetic color content (Ayni & Ningsih, 2021; Kishor et al., 2021; Sari et al., 2018; Setiawan et al., 2023; Sunoko, 2018). Therefore, there is a need for processing techniques or methods in this case. One of them uses membrane technology (Kiswanto & Rahayu, 2019).

✉ Corresponding author:
E-mail: maryudi@che.uad.ac.id

Membrane technology is the treatment of liquid waste, one of which is the treatment of textile wastewater (Faizal et al., 2022; Jiang & To, 2022; Korkut et al., 2024; Maulana & Marsono, 2021; Mu'aliyah et al., 2022). Compared to other separation processes, this treatment process has several advantages, including the use of membranes that do not change the structure or arrangement of the separated substances, are biopolymers, can be operated at room temperature, relatively low energy consumption, non-toxic, no chemical additives in the process, and is a clean technology (Aburideh et al., 2021; Bousbih et al., 2021; Harianingsih & Maharani, 2018; Masri et al., 2020; Sianipar et al., 2023; Wang et al., 2023), lower initial investment cost than conventional systems, can remove harmful substances from textile wastewater (Chen et al., 2022; Hartini et al., 2018; Jin et al., 2018; Khan et al., 2020; Maulana & Marsono, 2021; Osman et al., 2024; Wen et al., 2021). One of the techniques commonly used in this process is phase inversion.

Phase inversion itself is a method in membrane manufacturing where the polymer is converted from the liquid phase to the solid phase with a certain control mechanism (Khan et al., 2020; Sofyana et al., 2020). The phase inversion process occurs by evaporating the precipitating solvent. The phase separation mechanism that occurs can be explained by a three-phase diagram with three main components, namely polymer, solvent and non-solvent (Lusiana & Prasetya, 2020), as shown in Figure 1.




Figure1. phase diagram in phase inversion method.

There are many polymer derivatives that can be used in fabricating membranes including cellulose derivatives i.e. cellulose acetate propionate (CAP), cellulose acetate (CA). CAP is one of the biopolymer materials with the chemical formula $C_7H_{14}O_9$ (Cid, 2024) which is very potential to be applied to the manufacture of

bioplastics because it has biodegradable properties (Faizal et al., 2022; Jiang & To, 2022). CAP has the advantages of excellent transparency and strength, then the incorporation of propionyl groups gives CAP the properties of water resistance, good solubility and compatibility with other polymers, resulting in a balance of hydrophilic and hydrophobic properties (Abdellah et al., 2020; Aburideh et al., 2021; Ashter, 2018).

Many studies on membrane fabrications have been carried out using various types of polymeric materials. Biomaterials are preferably used in fabricating membrane i.e., cellulose acetate, chitosan (Abdellah et al., 2020; Thakur & Voicu, 2016). As time passes, one type of polymer that is rarely found as raw material of membrane is CAP, despite of cheaper price compared to others. Therefore, this research aims to study the preparation of CAP biopolymer-based membrane by phase inversion method and its application in treatment of textile wastewater containing remazol dye.

MATERIAL AND METHOD

Materials

There were several materials used in fabricating the membrane, including cellulose acetate propionate (CAP) from Sigma Aldrich, acetone (industrial grade), polyethylene glycol 4000 (PEG 4000), formaldehyde (industrial grade), and distilled water. In the application step, remazol dye was used.

Fabrication of cellulose acetate propionate membrane

In the manufacture of CAP membranes, three different compositions were prepared to produce membranes. The composition consisted of a mixture of CAP, PEG 4000, and acetone. The compositions are presented in Table 1.

Table 1. Compositions of CAP, PEG 4000, and acetone in producing CAP membrane.

No	CAP (%)	PEG 4000 (%)	Acetone (%)	Membrane Thickness (μm)
1	15	3	82	200
2	14	3	83	200
3	13	3	84	200




Figure 2. Procedure for CAP membrane preparation with phase inversion method.

The CAP membrane was made in several steps. In the first step, the membrane solution that consisted of CAP, PEG 4000, and acetone was stirred for 4 hours at 30 °C to obtain the dope solution. The CAP dope solution was allowed to stand for 12 hours. The dope solution was then printed with printing equipment (Four Sided Applicator Frame Type: V11 Film Coater) on a glass plate, then dipped in distilled water until the membrane was peeled off. The CAP membrane was dried at room temperature. The CAP membrane was given a thermal annealing treatment at a time of 60 seconds and at a temperature of 60°C before being applied for wastewater treatment. The CAP membrane manufacturing procedure using the phase inversion method is shown in Figure 2.

Membrane Characterization

Porosity analysis

The porosity analysis was carried out by using gravimetric method (Huang et al., 2017; Li et al., 2009). The porosity ε (%) was calculated by using Eq. (1).

$$\varepsilon = \frac{\omega_w - \omega_d}{A \cdot l \cdot d_w} \quad (1)$$

where ω_w is wet membrane weight (g), ω_d is dry membrane weight (g), A is membrane area (cm²), l is membrane thickness (cm), and d_w is density of water (g/cm³).

Flux analysis

The flux of CAP membrane was determined by using dead-end filtration unit. The penetration flux J (L/m².h) is defined as shown in Eq. (2) (Huang et al., 2017; Li et al., 2009).

$$J = \frac{Q}{A \cdot t} \quad (2)$$

where Q is permeate volume (L), A is area of membrane (m²), t is permeation time (h).

Rejection analysis

The CAP membrane was applied for the filtration process of artificial wastewater containing remazol dye. The experiment was carried out using a dead-end filtration unit. The artificial wastewater was prepared by dissolving remazol dye in the distilled water at concentrations of 5 ppm; 10 ppm; and 15 ppm. The rejection $R(\%)$ was calculated using Eq. (3) (Huang et al., 2017).

$$R = \left(1 - \frac{C_p}{C_f}\right) \times 100 \quad (3)$$

where C_p is permeate concentration, C_f is feed solution concentration.

RESULTS AND DISCUSSIONS

Porosity

Swelling or porosity analysis is carried out to determine the amount of substance absorbed by the membrane (Fadli et al., 2021; Febriasari et al., 2021; Khan et al., 2020; Lubis et al., 2023). The swelling magnitude of the CAP membrane is calculated using Eq. (1) and the results are presented in Figure 3.

Figure 3 shows that the higher porosity value is obtained at a lower CAP concentration. The higher the amount of substance will be absorbed by the CAP membrane at a higher porosity. This result is in accordance with the

results of previous research (Hartini et al., 2018) where the greater the porosity value, the greater the substance that can be absorbed by the membrane. According to some other previous research (Ismail et al., 2019; Lusiana & Prasetya, 2020), the higher the polymer concentrations used, the smaller the porosity value of the membrane.




Figure 3. Porosity of membrane with CAP concentration of 13%, 14%, and 15%.

Flux

Flux analysis is carried out using a dead-end filtration device to measure the flow rate of membrane permeate per unit area and time (Bousbih et al., 2021; Indarti et al., 2020; Lusiana & Prasetya, 2020; Asri et al., 2021; Rahmahwati et al., 2021). The following flux analysis results are presented in Figure 4.




Figure 4. Flux of membrane with CAP concentration of 13%, 14%, and 15%.

From Figure 4, it can be seen that the membrane concentration of 13% CAP has a higher flux value compared to concentration of 14%, and 15% CAP. This is in line with the porosity results conducted in this study. The flux results are also in accordance with the results that were reported previously (Bhernama et al., 2023; Fathanah & Meilina, 2021; Fransiska et al., 2023)

stated that the higher the membrane concentration, the lower the flux value produced.

Rejection

Measurement of the rejection value is carried out to determine the selectivity of the membrane or the ability of the membrane to withstand specimens passing through the membrane (Abu-Zurayk et al., 2023; Bhernama et al., 2023; Lubis et al., 2023; Maulana & Marsono, 2021; Morão et al., 2005; Reddy et al., 2022; Vasagar et al., 2021). The results of the rejection analysis with variations in CAP membrane concentration (13%; 14%; and 15%) and variations in waste dye concentration of 5, 10, and 15 ppm can be seen in Figure 5.




Figure 5. Rejection analysis results with varying CAP membrane concentrations (13%; 14%; and 15%) and varying effluent dye concentrations of 5, 10, and 15 ppm

The value of the rejection yield varies between 0% and 43.48%. Therefore, the rejection efficiency is also largely determined by the membrane pores (Reddy et al., 2022). In Figure 5, it can be seen that the highest rejection result is found in the CAP membrane with a membrane concentration of 13%, while the smallest rejection result is found in the CAP membrane with a concentration of 15%. This is in line with the previous result reported (Lindu et al., 2010) where researchers suggest that the greater the percentage value of membrane rejection is directly proportional to the resulting flux value.

CONCLUSIONS

This research shows that the use of cellulose acetate propionate (CAP) membrane is effective in treating wastewater containing remazol dye. The CAP membrane has a high porosity, as

well as flux that varies depending on CAP concentration. The CAP membrane has the effectiveness of reducing the concentration of remazol dye by 43%. The results also show that the membrane with 13% CAP concentration has higher performance than CAP membrane with 14% and 15% CAP concentration.

ACKNOWLEDGEMENTS

The authors would like to thank the members of Material Laboratory, Chemical Engineering Department, Universitas Ahmad Dahlan for their support in conducting this research. The authors also would like to convey their gratitude to Universitas Ahmad Dahlan for financial support through a research grant with contract number: PD-250/SP3/LPPM-UAD/VIII/2023

REFERENCES

- Abdellah, S. F., Lovert, A., Eman, A. W. 2020. Cellulose acetate, cellulose acetate propionate and cellulose acetate butyrate membranes for water desalination applications. *Cellulose*. 0123456789.
- Aburideh, H., Tigrine, Z., Zioui, D., Hout, S., Tassalit, D., Abbas, M. 2021. Wastewater treatment using a modified cellulose acetate membrane. *Cellulose Chemistry and Technology*. 55(5-6): 697–704.
- Abu-Zurayk, R., Alnairat, N., Khalaf, A., Ibrahim, A. A., Halaweh, G. 2023. Cellulose Acetate Membranes: Fouling Types and Antifouling Strategies—A Brief Review. *Processes*. 11(2): 489.
- Amelia, S., Shitopyta, L. M., W, M. U., Sriyana, I. 2023. Degradasi Warna Napthol Jeans dengan Fotokatalis TiO₂-SiO₂ dari Pasir Pantai Karangwuni Kulon Progo Color Degradation of Napthol Jeans with TiO₂-SiO₂ Photocatalyst from Karangwuni Beach Sand, Kulon Progo. *Eksergi*. 20(1): 15–20.
- Ashter, S. A. 2018. Chemistry of cellulosic polymers. *Technology and Applications of Polymers Derived from Biomass*. In *Plastics Design Library*. William Andrew Publishing. 57–74.
- Asri, M. A. N. M., Abd Halim, N. S., Wirzal, M. D. H., Mohd Yusoff, A. R., Bilad, M. R. 2021. Thermal Annealing Surface Modification: Effect on Surface and Performance of Electrospun Nylon 6,6 Nanofiber Membrane for Wastewater Treatment. *Jurnal Penelitian Dan Pengkajian Ilmu Pendidikan: E-Saintika*. 5(1): 56.
- Ayni, L. N., Ningsih, E. 2021. Pengolahan limbah cair tekstil dengan menggunakan koagulan FeCl₃. *Seminar Nasional Teknologi Industri Berkelanjutan I (SENASTITAN I)*. 370–377.
- Bhernama, B. G., Nurhayati, Saputra, S. A., Jihan Amalia. 2023. Characterization of Cellulose Acetate Membrane from Nutmeg Shells. *Jurnal Sains Natural*. 13(3): 152–160.
- Bousbih, S., Ammar, R. B., Amar, R. Ben, Dammak, L., Darragi, F., Selmane, E. 2021. Synthesis and evaluation of asymmetric mesoporous ptfе/clay composite membranes for textile wastewater treatment. *Membranes*. 11(11): 850.
- Chen, T., Wei, X., Chen, Z., Morin, D., Alvarez, S. V., Yoon, Y., Huang, Y. 2022. Designing energy-efficient separation membranes: Knowledge from nature for a sustainable future. *Advanced Membranes*. 2(May): 100031.
- Cid, P. C. L. 2024 Cellulose Acetate Propionate. National Center for Biotechnology Information. https://pubchem.ncbi.nlm.nih.gov/compound/Cellulose_acetate-propanoate#datasheet=LCSS. Accessed at 13 December 2023.
- Enrico, E. 2019. Dampak Limbah Cair Industri Tekstil Terhadap Lingkungan Dan Aplikasi Tehnik Eco Printing Sebagai Usaha Mengurangi Limbah. *MODA*. 1(1): 1–9.
- Fadli, M., Khausar, A., Sofyana, S., Fathanah, U. 2021. Karakteristik Membran Komposit Polietersulfon, Polivinilpirolidon dan Kitosan. *Jurnal Serambi Engineering*. 6(4): 2310–2319.
- Faizal, M., Jaksen, Fadarina. 2022 Sintesis dan Karakterisasi Selulosa Asetat dari Tanda

- Kosong Kelapa Sawit sebagai Bahan Baku Bioplastik. *Kinetika*. 13(2): 17–23.
- Fathanah, U., Meilina, H. 2021 Karakterisasi dan Kinerja Membran Polyethersulfone Termodifikasi Aditif Anorganik secara Blending Polimer. *Jurnal Serambi Engineering*. 6(4), 2407–2414.
- Febriasari, A., Huriya, Ananto, A. H., Suhartini, M., Kartohardjono, S. 2021. Polysulfone-polyvinyl pyrrolidone blend polymer composite membranes for batik industrial wastewater treatment. *Membranes*. 11(1): 1–17.
- Fransiska, D., Yuliati, S., Junaidi, R. 2023. Membran Selulosa Asetat Berbasis Nata De Coco Ditinjau Dari Pengaruh Penambahan Zat Aditif Polyethylene Glycol (PEG) Terhadap Permeabilitas (Fluks). *Jurnal Serambi Engineering*. 8(4): 7078–7085.
- Harianingsih, H., Maharani, F. 2018 Sintesis Membran Selulosa Asetat Cassava Untuk Mikrofiltrasi Fe Pada Limbah Batik Artifisial. *Jurnal Inovasi Teknik Kimia*. 3(2): 36 - 40.
- Hartini, A. S., Syahbanu, I., Nurlina. 2018. Uji water uptake dan porositas terhadap blend membran berbasis polisulfon dan selulosa asetat dari nata de coco. *Jurnal Kimia Khatulistiwa*. 7(4): 25–30.
- Huang, Y., Wang, Z., Yan, X., Chen, J., Guo, Y., Lang, W. 2017. Versatile polyvinylidene fluoride hybrid ultrafiltration membranes with superior antifouling , antibacterial and self-cleaning properties for water treatment. *Journal of Colloid And Interface Science*. 505: 38–48.
- Indarti, D., Putra, D. I., Piluharto, B., Setyawan, D. 2020 Blending Polymer Cellulose Acetate/Polysulfone for Resistance of Protein Fouling. *IOP Conference Series: Materials Science and Engineering*. 833(1): 012071.
- Ismail, M. I., Fadzil, M. S. M., Rosmadi, N. N. F., Razali, N. R. A. M., Mohamad Daud, A. R. 2019 Acid treated corn stalk adsorbent for removal of alizarin yellow dye in wastewater. *Journal of Physics: Conference Series*. 1349(1): 012105.
- Jiang, Z., To, N. 2022. Recent Advances in Chemically Modified Cellulose and Its Derivatives for Food Packaging Applications: A Review. *Polymers*. 14(8): 15 - 33.
- Jin, P., Huang, C., Li, Y., Li, J., Wang, L. 2018 Fabrication of a superhydrophobic poly(vinylidene fluoride) hollow fibre membrane by spray deposition. *Micro and Nano Letters*. 13(2): 223–227.
- Khan, B., Zhan, W., Lina, C. 2020 Cellulose acetate (CA) hybrid membrane prepared by phase inversion method combined with chemical reaction with enhanced permeability and good anti-fouling property. *Journal of Applied Polymer Science*. 137(47): 49556.
- Subagyo, P. K. 2021. Pengaruh Zat Pewarna Sintetis terhadap Pewarnaan Kain Batik. *Journal of Fashion Product Design & Business*. 2: 40–48.
- Kishor, R., Purchase, D., Saratale, G. D., Saratale, R. G., Ferreira, L. F. R., Bilal, M., Chandra, R., Bharagava, R. N. 2021. Ecotoxicological and health concerns of persistent coloring pollutants of textile industry wastewater and treatment approaches for environmental safety. *Journal of Environmental Chemical Engineering*. 9(2): 105012.
- Kiswanto, Rahayu, W. L. N. 2019. Pengolahan limbah cair batik menggunakan teknologi membran nanofiltrasi di kota pekalongan. *Litbang Kota Pekalongan*. 17: 72–82.
- Korkut, S., Ormanci-Acar, T., Keskin, B., Ağtaş, M., Karahan, Ö., Demir, T. U., Unal, S., Menciloglu, Y. Z., Koyuncu, I. 2024. Effect of Photocatalytic Pretreatment on the Membrane Performance in Nanofiltration of Textile Wastewater. *Water, Air, and Soil Pollution*. 235(5): 266.
- Li, J., Xu, Z., Yang, H., Yu, L., Liu, M. 2009. Applied Surface Science Effect of TiO₂ nanoparticles on the surface morphology and performance of microporous PES membrane. *Applied Surface Science*. 255: 4725–4732.
- Lindu, M., Puspitasari, T. R., Dian, A. 2010 Sintesis Dan Uji Kemampuan Membran Mikrofiltrasi Selulosa Asetat Dari Nata De Coco Untuk Penyisihan Kekeruhan Pada air Artifisial. *Jurnal Sains Materi Indonesia*. 12(3): 153–158.
- Lubis, M. R., Suraiya, S., Fazira, F., Dasmara, a. N. H., Zuhra, Z., Muhammad, a., Hidayat, M. H., Rosnelly, C. M.,

- Syamsuddin, Y., Sofyana, S., Fathanah, U. 2023 Fabrication of polyethersulfone ultrafiltration membrane for reducing organic compounds in water. *IOP Conference Series: Earth and Environmental Science*. 1183(1): 012065.
- Lusiana, R. A., Prasetya, N. B. A. 2020. Pengaruh Penambahan Aditif terhadap Karakterisasi Fisikokimia Membran Polisulfon. *Indonesian Journal of Chemical Science*. 9(3): 197.
- Masri, P. Al, Pinem, J. A., Saputra, E. 2020. Pengaruh Suhu Pemanasan Terhadap Performa Membran. *Journal Online Mahasiswa FTEKNIK*. 7(2): 1-4.
- Maulana, M. R., Marsono, B. D. 2021. Penerapan Teknologi Membran untuk Mengolah Limbah Cair Industri Tahu. *Jurnal Teknik ITS*. 10(2): 54-61.
- Morão, A., Escobar, I. C., De Amorim, M. T. P., Lopes, A., Gonçalves, I. C. 2005. Postsynthesis modification of a cellulose acetate ultrafiltration membrane for applications in water and wastewater treatment. *Environmental Progress*. 24(4): 367-382.
- Mu'aliyah, R., Budi, S., Kusuma, W. 2022 Synthesis of Cellulose Esters through an Oxidative Esterification of Cellulose with Cinnamaldehyde in Ionic Liquid and External Bases. *Indonesian Journal of Chemical Science*. 11(3): 266-276.
- Osman, A. I., Chen, Z., Elgarhy, A. M., Farghali, M., Mohamed, I. M., Priya, K., Hawash, H. B., Yap, P. 2024. Membrane Technology for Energy Saving : Principles , Techniques , Applications , Challenges , and Prospects. *Journal of Advanced Energy and Sustainability*. 2400011(February): 1-29.
- Rahmahwati, C. A., Muhyi, A., Salmiyah, Aiyub, S. 2021 Penggunaan Eceng Gondok Sebagai Bahan Tambahan Untuk Pembuatan Membran Desalinas. *Proceeding Seminar Nasional Politeknik Negeri Lhoksemawe*. 5(1): 146-151.
- Rahmiati, M., Wafiroh, S., Pudjiastuti, P. 2018. Pembuatan Dan Karakterisasi Membran Fotokatalitik Hollow Fiber Selulosa Asetat-TiO₂ Untuk Degradasi Remazol Red 198. *Jurnal Kimia Riset*. 3(1): 20 - 28.
- Reddy, A. S., Kalla, S., Murthy, Z. V. P. 2022. Textile wastewater treatment via membrane distillation. *Environmental Engineering Research*. 27(5): 210228.
- Rizkiah, R., Luciana, L. 2022. Optimasi Pengolahan Limbah Cair Textile Menggunakan Metode Sono-Fenton. *Sainteks: Jurnal Sains Dan Teknik*. 4(1): 1-10.
- Sari, D. A., Sukanta, S., Hakiim, A. 2018. Anaerobic Wastewater Treatments: Prediction of Retention Time on RT/RW Plant. *INSIST*. 3(1): 134.
- Sausan, F. W., Puspitasari, A. R., Yanuarita P, D. 2021 Studi Literatur Pengolahan Warna pada Limbah Cair Industri Tekstil Menggunakan Metode Proses Adsorpsi, Filtrasi, dan Elektrolisis. *Jurnal Tecnoscienza*. 5(2): 213.
- Setiawan, D. A., Marthin, R., Wanwol, D. T. 2023. Adsorption Of Remazol Brilliant Blue R Dye Using Activated Carbon From Empty Palm Oil Bunches. *Jurnal Sains Natural*. 13: 183-190.
- Sianipar, A. J., Widyaningsih, S., Suyata. 2023. Sintesis dan Uji Kinerja Membran Selulosa Termodifikasi Polistirena dari Ampas Tebu dengan Aditif Monosodium Glutamate untuk Menurunkan Nilai BOD dan COD Limbah Cair Tahu. *KOVALEN: Jurnal Riset Kimia*. 9(2): 183-194.
- Sofyana, Aprilia, S., Assaki, M. 2020. Karakteristik Membran Selulosa Triasetat Yang Dipreparasi Secara Inversi Fasa Presipitasi Imersi. *Jurnal Inovasi Ramah Lingkungan (JIRL)*. 1(1): 1-5.
- Sunoko, I. 2018. Analisis Lingkungan Dampak Pencemaran Air Limbah Batik Terhadap Kualitas Air Sumur Gali di Sentra Industri Batik Jenggot Kota Pekalongan. *ICENIS*. 09008.
- Thakur, V. K., Voicu, S. I. 2016. Recent advances in cellulose and chitosan based membranes for water purification: A concise review. *Carbohydrate Polymers*. 146: 148-165.
- Vasagar, V., Hassan, M. K., Khraisheh, M. 2021 Membrane surface modification and functionalization. *Membranes*. 11(1): 11-14.
- Wang, Z., Luo, X., Zhang, J., Zhang, F., Fang, W., Jin, J. 2023. Polymer membranes for

- organic solvent nanofiltration: Recent progress, challenges and perspectives. *Advanced Membranes*. 3(February): 100063.
- Wen, Y., Zhang, H., Li, J., An, S., Chen, W., Song, Y. 2021. Perakitan Inti-kulit Asam Heteropolimer dan Polimer: Efisien Pembuatan Selulosa Asetat Propionat dan Pengolahannya Produk. *Journal ACS Sustainable Chemistry & Engineering*. 9(14): 5179–5186.
- Yuniarizky, F., Nazriati. 2021. Adsorpsi Zat Warna Remazol Red menggunakan Nanokomposit Silika Aerogel-Karbon Aktif. *Journal Cis-Trans*. 5(2): 25–33.
- Yuniarti, B. I., Widayatno, T. 2022. Analisa Perubahan BOD, COD, dan TSS Limbah Cair Industri Tekstil Menggunakan Metode Elektrooksidasi-elektrokoagulasi Elektroda Fe-C dengan Sistem Semi Kontinyu. *Jurnal Rekayasa Hijau*. 5(3): 238–247.

Application of Cellulose Acetate Propionate Biopolymer Membrane in The Treatment of Textile Wastewater Containing Remazol Dye

ORIGINALITY REPORT

10%

SIMILARITY INDEX

PRIMARY SOURCES

1 Huaiying Zhang, Lifu Wu, Yanfen Zhang, Sai An, Haralampos N. Miras, Yu-Fei Song. "Heteropolyacids and sulfonic acid-bifunctionalized organosilica spheres for efficient manufacture of cellulose acetate propionate with high viscosity", *Cellulose*, 2020 24 words — 1%

[Crossref](#)

2 Wen Yu Pang, Abdul Latif Ahmad, Nur Dina Zaulkiflee. "Antifouling and antibacterial evaluation of ZnO/MWCNT dual nanofiller polyethersulfone mixed matrix membrane", *Journal of Environmental Management*, 2019 20 words — 1%

[Crossref](#)

3 Heba Abdallah, Tarek S. Jamil, A.M. Shaban, Eman S. Mansor, Eglal R. Souaya. "Influence of the polyacrylonitrile proportion on the fabricated UF blend membranes' performance for humic acid removal", *Journal of Polymer Engineering*, 2018 15 words — 1%

[Crossref](#)

4 Dimas Ilham Munada, Achmad Umar Sa'id, Alvi Surya Juniarianto, Billy Muhammad Luthfi et al. " Synthesis of Composite Photocatalyst Derived from Medical Mask Waste/TiO for Degradation of Rhodamine-B Textile Waste ", *Journal of Physics: Conference Series*, 2024 12 words — 1%

[Crossref](#)

5 Shahbaz Abbas, Lin Han Chiang Hsieh, Kuaanan Techato. "Supply chain integrated decision model in order to synergize the energy system of textile industry from its resource waste", Energy, 2021 11 words — < 1%

Crossref

6 Hadis Rostamabadi, Ilkem Demirkesen, Rosana Colussi, Swarup Roy et al. "Recent trends in the application of films and coatings based on starch, cellulose, chitin, chitosan, xanthan, gellan, pullulan, Arabic gum, alginate, pectin, and carrageenan in food packaging", Food Frontiers, 2024 10 words — < 1%

Crossref

7 Ruben Miranda, Raluca Nicu, Elena Bobu, Angeles Blanco. "Efficiency of Chitosan and their Combination with Bentonite as Retention Aids in Papermaking", BioResources, 2016 10 words — < 1%

Crossref

8 Nasrul Arahman, Widia Puspita Sari, Indah Maulana Sari, Cut Meurah Rosnelly et al. "The Effectiveness of Polyvinylidene Fluoride Membranes Modified with Poloxamer and Single/Multi-Walled Carbon Nanotubes for Lactalbumin Purification", ChemEngineering, 2022 9 words — < 1%

Crossref

9 Nghiem, L.D.. "Extraction and transport of metal ions and small organic compounds using polymer inclusion membranes (PIMs)", Journal of Membrane Science, 20060915 9 words — < 1%

Crossref

10 www.ippt.pan.pl 9 words — < 1%

Internet

11 Dewi Nur Fadhila, Alisha Zafirah Ridwan, Nur Aqilah Amir, Andi Abdillah, Ratih Kartini N, Hasanuddin H, Nursyamsi Djameluddin. "Mechanical properties and formulation of Hydrophilic fiber and shrimp shell combination as a novel eco-friendly dental restoration material", Heliyon, 2024

Crossref

8 words — < 1%

12 Meltem Ağtaş, Mehmet Dilaver, İsmail Koyuncu. "Halloysite nanoclay doped ceramic membrane fabrication and evaluation of textile wastewater treatment performance", Process Safety and Environmental Protection, 2021

Crossref

8 words — < 1%

13 Nasrul Arahman, Cut Meurah Rosnelly, Muhammad Prayogie Aulia, Rinal Dia'ul Haikal et al. "Exploring the effect of CNTs and Pluronic on Characteristics and Stability of Polyethersulfone (PES) and Polyvinylidene Fluoride (PVDF) Membranes", Case Studies in Chemical and Environmental Engineering, 2024

Crossref

8 words — < 1%

14 Sutrasno Kartohardjono, Ghofira Muna Khansa Salsabila, Azzahra Ramadhani, Irfan Purnawan, Woei Jye Lau. "Preparation of PVDF-PVP Composite Membranes for Oily Wastewater Treatment", Membranes, 2023

Crossref

8 words — < 1%

15 eprints.utar.edu.my

Internet

8 words — < 1%

16 jurnal.unimed.ac.id

Internet

8 words — < 1%

17 khazna.ku.ac.ae

Internet

8 words — < 1%

-
- 18 libweb.kpfu.ru 8 words — < 1%
Internet
-
- 19 pure.sruc.ac.uk 8 words — < 1%
Internet
-
- 20 s3-ap-southeast-1.amazonaws.com 8 words — < 1%
Internet
-
- 21 www.researchsquare.com 8 words — < 1%
Internet
-
- 22 Wan Nur Ain Shuhada Abdullah, Nadiene Salleha Mohd Nawi, Woei Jye Lau, Yeek Chia Ho, Farhana Aziz, Ahmad Fauzi Ismail. "Enhancing Physiochemical Substrate Properties of Thin-Film Composite Membranes for Water and Wastewater Treatment via Engineered Osmosis Process", *Polymers*, 2023 6 words — < 1%
Crossref

EXCLUDE QUOTES ON

EXCLUDE SOURCES OFF

EXCLUDE BIBLIOGRAPHY ON

EXCLUDE MATCHES OFF